

09/527,529
69605/99

2

IN THE CLAIMS:

Please revise the claims as follows:

1. (Currently amended) A liquid-crystal display comprising:

a liquid-crystal layer provided between a pair of substrates so as to be oriented to bend alignment; and

a phase compensation plate provided for an outside of each of the substrates, a retardation of a light passing through said liquid-crystal layer and said phase compensation plates being limited to a value $\frac{1}{2}$ or less of a minimum wavelength of said light relating to display; and

~~a circuit to selectively apply a voltage across said liquid-crystal layer, said voltage being equalized for all colors in said liquid-crystal display.~~
2. (Original Claim) The liquid-crystal display according to claim 1, wherein a birefringent index of a liquid-crystal molecule in said liquid-crystal layer is equal to or less than 0.16.
3. (Original Claim) The liquid-crystal display according to claim 1, wherein said minimum wavelength is based on a color having said minimum wavelength among colors relating to color display.
4. (Original Claim) The liquid-crystal display according to claim 3, wherein said minimum wavelength of said light is based on blue color.

09/527,529
69605/99

3

5. (Original Claim) The liquid-crystal display according to claim 3, wherein said minimum wavelength of said light ranges between 380 nm and 488 nm.
6. (Original Claim) The liquid-crystal display according to claim 4, wherein said minimum wavelength of said light ranges between 380 nm and 488 nm.
7. (Withdrawn - currently amended) A method of making a liquid crystal display, said liquid crystal display including a plurality of color filters on a first substrate, said color filters including a plurality of colors, a liquid-crystal layer provided between said color filters and a second substrate so as to be oriented to bend alignment, a phase compensation plate outside each of said first substrate and said second substrate, a plurality of electrodes associated with said color filters, and a circuit selectively providing a voltage to said electrodes, said method comprising:
- determining a color from said plurality of colors having a shortest wavelength; and
- forming said liquid-crystal display so that a retardation of a light passing through said liquid-crystal layer and said phase compensation plates is limited in range between zero and a value of $\frac{1}{2}$ a wavelength of said shortest wavelength during a predetermined range of said bend orientation state of said liquid-crystal layer; and
- ~~providing a same voltage level to be applied selectively to all of said plurality of electrodes.~~
8. (Withdrawn) The method of claim 7, wherein said shortest wavelength color corresponds to a blue color filter.

09/527,529
69605/99

4

9. (Withdrawn) The method of claim 7, wherein said shortest wavelength falls in a range between 380 nm and 488 nm.

10. (Currently amended) A liquid-crystal display comprising:

a first substrate;

a common electrode and a plurality of color filters on said first substrate, said color filters including a plurality of colors, one of said colors having a shortest color wavelength;

a second substrate supporting a plurality of electrodes;

a liquid-crystal layer provided between said color filters and said second substrate, said liquid-crystal layer having a predetermined range of driving voltages in a bend alignment orientation state; and

a phase compensation plate outside each of said first substrate and said second substrate,

wherein said liquid-crystal layer is formed such that, during said predetermined range of driving voltages, a retardation of a light passing through said liquid-crystal layer and said phase compensation plates is limited in range between zero and a value of $\frac{1}{2}$ of said shortest color wavelength, ~~allowing a single voltage level to be applied selectively to said electrodes.~~

11. (Currently amended) The liquid-crystal display of claim 10, wherein said shortest wavelength color corresponds to a blue color ~~filter~~.

12. (Currently amended) The liquid-crystal display of claim 10, wherein said shortest wavelength falls in a range between 380 nm and 488 nm.

09/527,529
69605/99

5

13. (New) The liquid-crystal display of claim 1, further comprising:

a circuit to selectively apply a voltage across said liquid-crystal layer, said voltage being equalized for all colors in said liquid-crystal display.

14. (New) The liquid-crystal display of claim 1, wherein a birefringent index of a liquid-crystal molecule in said liquid-crystal layer is set so that said liquid-crystal operates in an optically compensated birefringence (OCB) mode.

15. (New) The liquid-crystal display according to claim 1, wherein said minimum wavelength is based on a color having said minimum wavelength among colors relating to color display as determined by color filters comprising said liquid-crystal display and a filter having said minimum wavelength has a transmittance peak at approximately 430 nm wavelength as a blue light.

16. (New) The liquid-crystal display according to claim 15, wherein said blue light color filter comprises a first filter color of said liquid-crystal display, said liquid-crystal display further comprising a second color filter and said second color filter is for a red color having a transmittance peak at approximately 640 nm.

17. (New) The liquid-crystal display of claim 10, wherein a single power supply is used to selectively apply voltages to said plurality of electrodes

09/527,529
69605/99

6

18. (New) The liquid-crystal display of claim 10, wherein a birefringent index of a liquid-crystal molecule in said liquid-crystal layer is set so that said liquid-crystal operates in an optically compensated birefringence (OCB) mode.

19. (New) The liquid-crystal display according to claim 10, wherein said minimum wavelength is based on a color having said minimum wavelength among colors relating to color display as determined by color filters comprising said liquid-crystal display and a filter having said minimum wavelength has a transmittance peak at approximately 430 nm wavelength as a blue light.

20. (New) The liquid-crystal display according to claim 19, wherein said blue light color filter comprises a first filter color of said liquid-crystal display, said liquid-crystal display further comprising second color filter for a red color having a transmittance peak at approximately 640 nm.